



Uniflair IDWV – IUWV – IXWV

Highly efficient Water-Cooled
Direct Expansion
with Variable Speed Drive
Compressors
50 kw to 150 kW



se.com

Life Is On

Schneider
Electric



Schneider Electric: Your Partner in Sustainable Data Center Cooling

At Schneider Electric, we are committed to providing innovative and sustainable solutions that help organizations reduce their environmental impact and operational costs.

Our Uniflair Room Cooling units are designed with eco-efficiency in mind, utilizing advanced technologies to minimize energy consumption while maintaining peak performance.

System Architecture: standard features

Air filters

- Standard high-efficiency EU4-pleated air filters housed in a dedicated plenum box (IDWV, IXWV models)
- Dirty filter differential pressure switch
- Low airflow differential pressure switch

Cooling coil

- Heat exchanger coils designed for high sensible heat ratio (SHR) and reduced pressure drops
- Made from copper tubes mechanically expanded on aluminum fins
- Hydrophilic coil coating

Electronically Commuted fans

- High-tech compound material impellers with optimized flow control
- High efficiency EC motors
- Low power consumption
- High part-load efficiency
- Fan speed regulation by Modbus signal

Electrical panel

- Three-phase power supply 400 V/3 Ph+N/50 Hz for all the units with a single or a double power supply
- Low voltage secondary circuit 24 Vac with isolation transformer
- Metal isolating screen for protection from live components
- General isolator with mechanical interlock
- Thermo magnetic circuit-breakers for protection
- Terminal board for no-voltage signal and control contacts

Brushless VSD scroll compressor

- Discharge temperature control
- High energy efficiency at partial load
- Low starting current
- No sliding contacts

New microprocessor controller

- 7-inch, touch-screen LCD display interface
- Integrated management of the EEV and refrigerating circuit parameters
- Integrated Unloading logic on VSD units
- Full management of the condenser status including single fan status
- Grouping logic integrated
- RS485 and TCP/IP card bus integrated targeting the main communication protocols
- Native communication with EcoStruxure
- USB and Service port integrated in the display interface

Frame

- Self-supporting frame in galvanized steel with panels
- External panels coated with RAL9003 epoxy-polyester paint
- Internal panels with captive screws
- Internally lined with heat and sound-proofing insulation
- Refrigeration circuit inspection with unit active
- Side panels with coil inspection opening

Brazed plate condenser

- Design for maximizing energy efficiency
- Made of stainless steel



Main configurable options

Power supply

- Single power supply
- Double power supply with automatic commutation to provide redundancy and ensure a constant power supply

Construction options

- Downflow units (IDWV): top air return with bottom or front discharge (without additional floor stands)
- Upflow units (IUWV): front or bottom air return with top discharge
- Underfloor units (IXWV): top air return with bottom supply with multiple fan module configurations
- Standard, cleanable or low conductivity humidifier (cooling + humidification configuration)
- Condensate drain pump (cooling only and cooling + dehumidification configurations)
- Standard electrical heaters with extended fins, complete with double safety thermostat and manual resetting
- EU4 (standard) or EU5 air filters with or without motorized damper
- Power phase capacitors (not available for I*AV1511A models)
- Energy meter and CO₂ emission calculator
- Automatic Floor Pressurization System through Active Floor Control (AFC)

Additional accessories

- Suction from the top and front discharge plenums: they can be equipped with soundproofed insulation or with high efficiency air filters
- Back and top suction direct free-cooling plenum
- Floor stands (200mm height)
- Floor stands with motorized damper (500mm height)
- Motorized damper
- Adjustable baseframe (200 – 600 mm)
- Fire and smoke sensors
- Water leak detector
- Room air temperature / humidity sensor

Fan module configurations (only IXWV models)

- Fan module with bottom supply
- Fan module with rear supply
- Fan module with front supply
- Fan module with front and side supply
- Fan module with fully open supply



Air-cooled remote condensers (OCC)

- Pressostatic valve to vary the water flow through the brazed plate heat exchanger to control the condensing temperature and let the compressor operate within its own operating envelope with the highest efficiency
- Condensing pressure regulation valve (flooding valve) to maintain a minimum condensing pressure even with low water inlet temperature. The flooding 3-way valve is installed at the outlet of the condenser

Uniflair Room Cooling Direct Expansion IDWV-IUWV-IXWV

Technical Data

IDWV / IUWV models		1511A	1922A	2022A	2422A	2922A	3822A
Fan type	EC backward-curved centrifugal motor fan						
Power supply	V/ph/Hz	400 / 3ph / 50 Hz					
Fans	nr.	2	2	2	2	2	3
Air flow	m ³ /h	16800	16800	17000	20000	26000	27000
Gross total cooling capacity ¹	kW	68,0	79,2	83,1	110,2	126,5	160,8
EER		4,7	5,4	5,9	4,9	5,1	4,8

1: Data refer to nominal conditions: Room at 35 °C – 30% RH, outlet/inlet water temperature 35/30 °C, 0% glycol.

Dimensions

IDWV / IUWV models		1511A	1922A	2022A	2422A	2922A	3822A
Height (IDWV)	mm	2150	2150	2150	2150	2150	2150
Height (IUWV)	mm	1950	1950	1950	1950	1950	1950
Length	mm	1777	1777	1777	2082	2082	2650
Depth	mm	900	900	900	900	900	900

Technical Data

IXWV models		2322A	2622A	4022A
Fan type	EC backward-curved centrifugal motor fan			
Power supply	V/ph/Hz	400 / 3ph / 50 Hz		
Fans	nr.	2	2	3
Air flow	m ³ /h	18800	23400	30000
Gross total cooling capacity ¹	kW	109,0	124,2	171,1
EER		5,0	5,1	5,1

1: Data refer to nominal conditions: Room at 35 °C – 30% RH, outlet/inlet water temperature 35/30 °C, 0% glycol.

Dimensions

IXWV models		2322A	2622A	4022A
Height (without fan module)	mm	2150	2150	2150
Fan module height	mm	565	565	565
Length	mm	1777	2082	2650
Depth	mm	900	900	900

Life Is On



To learn more about Uniflair Cooling contact your Schneider Electric representative or visit se.com/cooling

Schneider Electric SE
35 rue Joseph Monier
92500 Rueil Malmaison – France
se.com

© 2024

Schneider Electric. All Rights Reserved. Schneider Electric | Life is On, EcoStruxure, Facility Expert, Facility Advisor are trademarks and the property of Schneider Electric SE, its subsidiaries and affiliated companies